Central Missouri Speedway Safety Checklist - B-Mod, Super Stock, Pure Stock, Midwest Mod
Driver: Car #: Date:
Front and Rear Firewall Sealed? Y/N
Tow Hook attached to chassis and accessible? Y/N
Overflow Tube pointed down and inside frame? Y/N
Correction needed
Fuel Cell mounted using 2" steel straps? Y/N
Tip-Over Valve and flapper? Y / N
Weights painted white with two ½" bolts and car number? Y/N
Correction needed
Driver's head with helmet 2" below roll bar? Y/N
Roll Bar Padding around Halo? Y/N
Window Net Installed and secured? Y/N
Kill Switch located behind driver's seat, labeled, and working? Y/N
Correction needed
Drive Shaft Loop ¼" by 2" steel 6" from front of drive shaft? Y/N
Drive Shaft painted white? Y / N
Coil Springs tethered to chassis? Y / N - Correction needed
Battery securely mounted and covered if in cockpit? Y/N
Correction needed
5-Point Racing Harness with 3-inch wide shoulder and lap belts and 2-inch wide
crotch strap? Belts current within last two years? Y/N
Does driver have proper Fire Suit, Gloves, Shoes, and Neck Brace/HANS device
with SFI label? Y/N
SA2015 or newer Helmet? Y/N
Wrap around racing seat? Y/N
Correction(s) needed: